AQH Aquatic Hose

Description
A lightweight PVC hose, reinforced with a semi-rigid crush resistant white PVC helix. It is tough, flexible and extremely durable under normal operating conditions. The cross section is maintained even when highly flexed. Minimum frictional loss is achieved by the smooth bore.

Applications
Ideally suited to light duty applications for garden ponds & aquatic installations.

Construction
Manufactured from a white rigid crush resistant anti-shock PVC Spiral helix encapsulated in a black flexible PVC cover, with a smooth inside wall.

Colour
Standard - Black, White Helix

Size Range
½" to 2"

Standard Length
30 metres supplied in a coil

Temperature Range
-15°C to +65°C

PRODUCT REF.	INTERNAL DIA mm	WORKING PRESSURE BAR	MIN BENDING RADIUS mm	WEIGHT Kg/Mtr	COIL LENGTH METRES
AQH05	12.6	2.0	16	0.08	30
AQH06	16.0	2.0	20	0.11	30
AQH07	19.0	2.0	24	0.15	30
AQH10	25.0	2.0	31	0.17	30
AQH12	32.0	2.0	40	0.25	30
AQH15	38.0	2.0	48	0.32	30
AQH20	51.0	1.0	64	0.43	30



CD Water Delivery Hose

Description
A lightweight PVC hose, reinforced with a semi-rigid crush resistant white PVC helix. It is tough, flexible and extremely durable under normal operating conditions. It has outstanding resistance to the effects of weather. Minimum frictional loss is achieved by the smooth bore.

Applications
Delivery and light duty suction of water, slurries and powders. This product is particularly popular in the agricultural, horticultural, marine and construction industries.

Construction
White rigid crush resistant anti-shock PVC spiral helix encapsulated in a flexible PVC cover, with a smooth inside wall.

Colour
Standard - Transparent Green, White Helix
Transparent Yellow, White Helix
Black, White Helix

Size Range
1" to 4"

Standard Length
30 metres / supplied in a coil

Temperature Range
-15°C to +65°C

PRODUCT REF.	INTERNAL DIA mm	WORKING PRESSURE BAR	MIN BENDING RADIUS mm	WEIGHT Kg/Mtr	COIL LENGTH METRES
CD05	12.6	10.0	57	0.16	30
CD06	16.0	9.5	72	0.26	30
CD07	19.0	9.0	86	0.28	30
CD10	25.4	8.0	114	0.33	30
CD12	31.8	7.0	143	0.46	30
CD15	38.0	6.5	171	0.55	30
CD20	51.0	6.0	230	0.81	30
CD25	63.0	5.0	284	1.04	30
CD30	76.0	4.0	342	1.38	30
CD35	89.0	4.0	401	1.80	30
CD40	102.0	4.0	459	2.16	30

CDFG Non-Toxic Delivery Hose

Description
A lightweight clear non-toxic PVC hose, reinforced with a semi-rigid crush resistant white PVC helix. It is tough, flexible and extremely durable under normal operating conditions. It has outstanding resistance to the effects of weather. Minimum frictional loss is achieved by the smooth bore.

Applications
Delivery and light duty suction of foodstuffs, water, slurries and powders.

Construction
White rigid crush resistant anti-shock PVC spiral helix encapsulated in a transparent flexible PVC cover, with a smooth inside wall.

Colour
Standard - Transparent, White Helix

Size Range
1" to 4"
CUFG available up to 6"

Standard Length
30 metres / supplied in a coil

Temperature Range
-15°C to +65°C

PRODUCT REF.	INTERNAL DIA mm	WORKING PRESSURE BAR	MIN BENDING RADIUS mm	WEIGHT Kg/Mtr	COIL LENGTH METRES
CDFG05	12.6	10.0	57	0.16	30
CDFG06	16.0	9.5	72	0.26	30
CDFG07	19.0	9.0	86	0.28	30
CDFG10	25.4	8.0	114	0.33	30
CDFG12	31.8	7.0	143	0.46	30
CDFG15	38.0	6.5	171	0.55	30
CDFG20	51.0	6.0	230	0.81	30
CDFG25	63.0	5.0	284	1.04	30
CDFG30	76.0	4.0	342	1.38	30
CDFG35	89.0	4.0	401	1.80	30
CDFG40	102.0	4.0	459	2.16	30



CDXE Super Elastic, Water Delivery Hose

Description
A lightweight PVC hose, manufactured from super elastic compounds to give increased flexibility, reinforced with a semi-rigid crush resistant white PVC helix. It is tough, flexible and extremely durable under normal operating conditions. It has outstanding resistance to the effects of weather. Minimum frictional loss is achieved by the smooth bore.

Applications
Delivery and light duty suction of water, slurries and powders. This product is particularly popular in the agricultural, horticultural, marine and construction industries.

Construction
White rigid crush resistant anti-shock PVC spiral helix encapsulated in a flexible super elastic PVC cover, with a smooth inside wall.

Colour
Standard - Transparent Green, White Helix Black, White Helix

Size Range
1" to 4"

Standard Length
30 metres / supplied in a coil

Temperature Range
-15°C to +65°C

PRODUCT REF.	INTERNAL DIA mm	WORKING PRESSURE BAR	MIN BENDING RADIUS mm	WEIGHT Kg/Mtr	COIL LENGTH METRES
CDXE05	12.6	10.0	50	0.17	30
CDXE06	16.0	9.5	64	0.20	30
CDXE07	19.0	9.0	76	0.28	30
CDXE10	25.4	8.0	102	0.39	30
CDXE12	31.8	7.0	127	0.47	30
CDXE15	38.0	6.5	152	0.56	30
CDXE20	51.0	6.0	204	0.82	30
CDXE25	63.5	5.0	254	1.07	30
CDXE30	76.0	4.0	304	1.36	30
CDXE35	89.0	4.0	356	1.79	30
CDXE40	101.6	4.0	406	2.13	30

CSH Sanitation Hose

Description
A lightweight PVC hose, manufactured from an odour resistant material reinforced with a semi-rigid crush resistant white PVC helix. It is tough, flexible and extremely durable under normal operating conditions. It has outstanding resistance to the effects of weather. Minimum frictional loss is achieved by the smooth bore.

Applications
Designed for the transportation of liquids & slurry within the marina, boat & caravan market places. This hose is resistant to most cleaning chemicals and detergents.

Construction
White rigid crush resistant anti-shock PVC spiral helix encapsulated in a white permeation resistant flexible PVC cover, with a smooth inside wall.

Colour
Standard - White, White Helix

Size Range
3/4" to 2"

Standard Length
30 metres / supplied in a coil

Temperature Range
-15°C to +65°C

PRODUCT REF.	INTERNAL DIA mm	WORKING PRESSURE BAR	MIN BENDING RADIUS mm	WEIGHT Kg/Mtr	COIL LENGTH METRES
CSH07	19.0	9.0	76	0.28	30
CSH10	25.4	8.0	102	0.39	30
CSH12	31.8	7.0	127	0.47	30
CSH15	38.0	6.5	152	0.56	30
CSH20	51.0	6.0	204	0.82	30