



T-412 LE  
MILK TANKER 10 BAR (150 PSI) - HARD WALL  
FDA ARRETE DU 09/11/94 A



- : WHITE NR
- : HIGH TENSILE TEXTILE CORDS WITH EMBEDDED STEEL HELIX WIRE
- : BLUE SBR/EPDM - ABRASION, OZONE AND OIL RESISTANT
- : LIQUID FOOD SUCTION AND DELIVERY. SPECIAL CONSTRUCTION FOR MAXIMUM FLEXIBILITY IN MILK TANKER APPLICATIONS. STERILIZE WITH 5% SODA SOLUTION.
- : 3:1
- : -30°C +80°C (-22°F +176°F)
- : ALFAGOMMA -ITALY- T-412 10 BAR (150 PSI) - MILK TANKER S&D (logo)
- : BLACK LETTERS

APPROVALS : IANESCO

Code	ID mm	ID inch	OD mm	Wall mm	Weight g/m	WP bar	WP psi	Vac. %	BR mm	Available Length m	Stock Length m
<a href="#"><u>412LE025354FGO</u></a>	25	1"	35	5	630	10	150	100	50	20	
<a href="#"><u>412LE032424FGO</u></a>	32	1" 1/4	42	5	780	10	150	100	64	20	
<a href="#"><u>412LE038484FGO</u></a>	38	1" 1/2	48	5	970	10	150	100	76	20	
<a href="#"><u>412LE040504FGO</u></a>	40	1" 9/16	50	5	1020	10	150	100	80	20	
<a href="#"><u>412LE042524FGO</u></a>	42	1" 5/8	52	5	1060	10	150	100	88	20	
<a href="#"><u>412LE045554FGO</u></a>	45	1" 3/4	55	5	1130	10	150	100	90	20	
<a href="#"><u>412LE051614FGO</u></a>	51	2"	61	5	1330	10	150	100	100	20	20
<a href="#"><u>412LE063754FGO</u></a>	63	2" 1/2	75	6	1890	10	150	100	126	20	20
<a href="#"><u>412LE076884FGO</u></a>	76	3"	88	6	2730	10	150	90	228	20	20
<a href="#"><u>412LE102164FGO</u></a>	102	4"	116	7	3610	10	150	90	306	20	