



**T-750 AA  
SANDBLAST 10 BAR (150 PSI)**



TUBE : BLACK CONDUCTIVE NR - ABRASION RESISTANT  
 REINFORCEMENT : HIGH TENSILE TEXTILE CORDS  
 COVER : BLACK CONDUCTIVE SBR/NR - ABRASION AND OZONE RESISTANT - PIN PRICKED  
 APPLICATION : SANDBLAST.  
 SAFETY FACTOR : 3:1  
 TEMPERATURE : -30°C +80°C (-22°F +176°F)  
 BRAND TEXT : ALFAGOMMA -ITALY- T-750 10 BAR (150 PSI) SANDBLAST (omega)  
 BRAND TYPE : WHITE LETTERS  
 APPROVALS :

NOTE : TOLERANCES ACCORDING TO "RMA" CLASS 311-A

Code	ID mm	ID inch	OD mm	Wall mm	Weight g/m	WP bar	WP psi	Vac. %	BR mm	Available Length m	Stock Length m
<u>750AA019337R03</u>	19	3/4	33	7	670	10	150			61	61
<u>750AA019357R03</u>	19	3/4	35	8	790	10	150			61	
<u>750AA019387R03</u>	19	3/4	38	9,5	930	10	150			15,25 / 30,5 / 61	
<u>750AA025407R03</u>	25	1"	40	7,5	820	10	150			40 / 61	61
<u>750AA025487R03</u>	25	1"	48	11,5	1440	10	150			15,25 / 30,5	
<u>750AA032487R03</u>	32	1" 1/4	48	8	1180	10	150			40 / 61	61
<u>750AA032557R03</u>	32	1" 1/4	55	11,5	1730	10	150			15,25 / 30,5 / 61	
<u>750AA038557R03</u>	38	1" 1/2	55	8,5	1540	10	150			61	61
<u>750AA038607R03</u>	38	1" 1/2	60	11	1960	10	150			15,25 / 30,5	
<u>750AA040607R03</u>	40	1" 9/16	60	10	1810	10	150			40	
<u>750AA051717R03</u>	51	2"	71	10	2210	10	150			40 / 61	61
<u>750AA051737R03</u>	51	2"	73	11	2490	10	150			15,25 / 30,5 / 61	