

T-350 AA
 STEAM 7 BAR (100 PSI) / HOT WATER 15 BAR (225 PSI)
 EXCEEDS BS 5122/A2



TUBE : BLACK EPDM
 REINFORCEMENT : HIGH TENSILE TEXTILE CORDS
 COVER : BLACK EPDM - HEAT, ABRASION AND OZONE RESISTANT
 APPLICATION : SATURATED STEAM AND HOT WATER DELIVERY IN GENERAL INDUSTRIAL APPLICATIONS.
 SAFETY FACTOR : ACCORDING TO BS 5122/A2
 TEMPERATURE : -40°C +165°C (-40°F +330°F)
 BRAND TEXT : ALFAGOMMA -ITALY- T-350 7 BAR (100 PSI) STEAM 165°C (330°F)
 BRAND TYPE : RED LETTERS
 APPROVALS :

NOTE :

Code	ID mm	ID inch	OD mm	Wall mm	Weight g/m	WP bar	WP psi	Vac. %	BR mm	Available Length m	Stock Length m
<u>350AA013233ND0</u>	13	1/2	23	5	370	7	100			61	61
<u>350AA016263ND0</u>	16	5/8	26	5	430	7	100			61	61
<u>350AA019313ND0</u>	19	3/4	31	6	610	7	100			20 / 61	61
<u>350AA025373ND0</u>	25	1"	37	6	750	7	100			61	61
<u>350AA030443ND0</u>	30	1" 3/16	44	7	900	7	100			61	
<u>350AA032463ND0</u>	32	1" 1/4	46	7	950	7	100			61	61
<u>350AA038523ND0</u>	38	1" 1/2	52	7	1100	7	100			20 / 61	61
<u>350AA040543ND0</u>	40	1" 9/16	54	7	1150	7	100			61	61
<u>350AA051673ND0</u>	51	2"	67	8	1700	7	100			20 / 61	61