

# SUPERFLEXTRACT

## PRODUCT DESCRIPTION

A versatile ducting with a wall of plasticised PVC axial and helical reinforcing yarns, supported by a PVC-coated spring steel helix.

A highly flexible, robust ducting which has many uses, including air handling and dust and fume extraction. It is particularly suitable for domestic and industrial vacuum cleaners because of its easy handling properties and its attractive appearance.

It is available to special order in a variety of colours, and with coloured yarns.



## FEATURES

**Lightweight:** light in weight and easy to handle.

**Flexible:** the multi-ply construction supported by a spring steel helix results in a highly flexible ducting. The product will not kink on sharp bends - ensuring maximum air flow at all times.

**Good Abrasion Resistance:** the double-walled construction gives good abrasion resistance.

**High Tensile Strength:** the axial and helical yarns give the ducting high tensile strength and excellent flex life.

**Standard length:** 15metres  
(76mm diameter standard length is 10 metres)

**Colour:** black with white yarns. A variety of customer specific colour options are also available.

**Temperature Range:** -5°C to +80°C at 20°C ambient.

**End Finishes:** Available with a wide range of injection moulded cuffs.

Nominal Bore (mm)	Total Weight (g/m)	Inside Radius (mm)	Working Pressure (kPa)	Working Vacuum (mmHg)
25	224	12	105	685
29	241	12	100	680
32	269	15	100	680
35	338	15	100	650
38	367	20	95	600
41	398	20	95	570
44	427	20	90	540
51	487	20	90	440
64	608	30	80	320
76	850	35	95	400

Items shown above are stock items.  
Other diameters are available - please contact us for more details.

FUME  
EXTRACTION

VACUUM CLEANERS  
DUST EXTRACTORS